



EN 13229
BlmSchV Stufe 2
Regensburger BStV / Aachener BStV / Munchener BStV
/ LRV
4 stelle DM.186



- *APERTURA FOCOLARE PER RIVESTIMENTO
- A** SEMITRANCIO VENTILAZIONE NATURALE
 - B** SEMITRANCIO Ø100-150
 - C** INGRESSO ARIA COMBURENTE Ø 150

(Max) nominal heat output	13.2 kW
Efficiency at Max	80.2 %
Energy Efficiency Class (A++ / G scale)	A
Energy Efficiency Index (EEI)	106 %
Seasonal space heating energy efficiency (ηs)	70 %
Temperature of exhaust smoke at Max	247 °C
Particulate/OGC / Nox (nominal at 13%O2)	27 - 65 - 103 mg/Nm3
CO at 13% O2 at Min and at Max	- 0.09 %
CO2 at Min and at Max	- 8.2 %
Mass of smoke at Min and at Max	- 12.9 g/sec
Fuel dimensions	L 250 ÷ 330mm
Pellet hourly consumption	- 3.8 kg/h *
Heatable volume m3	240 - 377 - 660 **
Combustion air inlet	Ø 150 mm
Smoke outlet	Ø 200 mm
Distance from combustible material (back/side/under)	160 mm / 600 mm / 220 mm
Distance from combustible material (front/ceiling)	800 mm / 1200 mm

* Data that may vary depending on the type of pellets used.

**Heatable volume based on the requested power per m3 (respectively 55-35-20 W/m3)